326 IAC 2-9-11 Automobile refinishing operations

Authority: IC 13-14-8; IC 13-15-2; IC 13-17-3-4; IC 13-17-3-11

Affected: IC 13-15; IC 13-17

Sec. 11.

- (a) The following definitions apply throughout this section:
- (1) "Automobile refinishing" is defined at 326 IAC 8-10-2(5).
- (2) A "solvent containing material" means any product used in automobile refinishing operations that contains volatile organic compounds (VOC) or hazardous air pollutants (HAP), including, but not limited to, the following:
- (A) Pretreatment wash primers.
- (B) Precoats.
- (C) Primers.
- (D) Primer surfacers.
- (E) Primer sealers.
- (F) Topcoats.
- (G) Specialty coatings.
- (H) Surface preparation products.
- (I) Gun cleaning solutions.
- (J) Paint removers.
- (K) Degreasing solvents.
- (L) Hardeners.
- (M) Catalysts.
- (N) Reducers.
- (O) Other additives.
- (b) An owner or operator of an automobile refinishing shop may elect to comply with this section by complying with the requirements of section 1 of this rule and the following conditions:
- (1) The requirements of 326 IAC 8-10, if applicable.
- (2) One (1) of the following:
 - A) The total amount of all solvent containing material delivered to the automobile refinishing shop, less the amount of solvent containing material quantified by manifest as having been shipped off-site, shall not exceed two thousand (2,000) gallons annually.
 - (B) The total amount of all solvent containing material delivered to the automobile refinishing shop that meets the VOC limits of 326 IAC 8-10-4(b), less the amount of solvent containing material quantified by manifest as having been shipped off-site, shall not exceed three thousand (3,000) gallons annually.